

16/18 new



fiorentini




16/18^{new}

TECHNICAL SPECIFICATION		16B new	18B new	16BT new	18BT new
Scrubbing width	mm	410	450	410	450
Cleaning capacity up to	m ² /h	1800 m ² /h	2200 m ² /h	1800 m ² /h	2200 m ² /h
Operating range	h	3	3	3	3
Solution tank capacity	l	30	30	30	30
Recovery tank capacity	l	30	30	30	30
TECHNICAL DATES					
Mechanical drive (front/rear)		ant.	ant.	post.	post.
Forward speed	km/h	0 - 4	0 - 4	0 - 4	0 - 4
Noise level	dB	72	72	72	72
ELETTRIC DATES					
Vacuum motor	w	24 v 500 w	24 v 500 w	24 v 500 w	24 v 500 w
Brush motor	w	1 x 24 v 500 w	1 x 24 v 500 w	1 x 24 v 500 w	1 x 24 v 500 w
Traction motor	w	/	/	24v 150w	24v 150w
Voltage		24 v (2x 12v - 110 Amp/h)	24 v (2x 12v - 110 Amp/h)	24 v (2x 12v - 110 Amp/h)	24 v (2x 12v - 110 Amp/h)
DIMENSION & WEIGHT					
Length	mm	800	800	800	800
Width	mm	430	460	430	460
Height	mm	900	900	900	900
Number of brushes and diameter	mm	1 x Ø 410	1 x Ø 450	1 x Ø 410	1 x Ø 450
Squeegee width	mm	670	670	670	670
Weight of the machine (without batteries/water/operator)	kg	60	60	60	60



ING. O. FIORENTINI s.r.l.

“THE BEST IN FLOOR MACHINES”
 afiorentini@ingfiorentini.it sales@ingfiorentini.it
 www.ingfiorentini.it

FILIALI:
 20132 MILANO – Fax. 02/2592779
 Via Palmanova 211/a – Tel. 02/27207783 - 2564810
 00155 ROMA – Fax. 06/22754075
 Via Carlo Carrà 13 – Tel. 06/22754040-2275060

STABILIMENTO:
 50030 PIANCALDOLI (FI) – Fax. 055/817144
 Loc. Rombola - Tel. 055/8173610

Distributed by:

