



DELUX



fiorentini


ING. O. FIORENTINI s.r.l.

“THE BEST IN FLOOR MACHINES”
a fiorentini@ingfiorentini.it sales@ingfiorentini.it
www.ingfiorentini.it

FILIALI:
20132 MILANO – Fax. 02-2592779
Via Palmanova 211/a – Tel. 02-27207783 - 2564810
00155 ROMA – Fax. 06-22754075
Via Carlo Carrà 13 – Tel. 06-22754040-2275060
STABILIMENTO:
50030 PIANCALDOLI (FI) – Fax. 055-817144
Loc. Rombola - Tel. 055-8173610

Distributed by:



DELUX

MODEL TECHNICAL SPECIFICATION		DELUX 43 B	DELUX 43 E	DELUX 43 ET	DELUX 43 BM	DELUX 50 B	DELUX 50 E
Scrubbing width	mm	430	430	430	430	500	500
Cleaning capacity up to	m ² /h	1500	1500	1500	1500	1700	1700
Operating range	h	2/3	/	/	2/3	2/3	/
Solution tank capacity		45	45	45	45	45	45
Recovery tank capacity	l	45	45	45	55	45	45

TECHNICAL DATES

Mechanical drive (front/rear)		rear	manual	rear	rear	rear	manual
Forward speed	km/h	0/3.5	0/3.5	0/3.5	0/3.5	0/3.5	0/3.5
Max. slope	%	10	10	10	10	10	10
Water lift	(mm H ₂ O)	1500	1800	1800	1500	1500	1800
Brush pressure	kg	20/40	20/40	20/40	20/40	25/45	25/45
Noise level	dB	72	72	72	72	72	72

ELECTRIC DATES

Power	v	24	230	230	24	24	230
Vacuum motor		24v 550w	230v 550w	230v 550w	24v 550w	24v 550w	230v 550w
Brush motor		24v 500w	230v 550w	230v 550w	24v 500w	24v 500w	230v 550w
Traction motor		24v 100w	/	/	24v 100w	24v 100w	/
Voltage		2x 12v 110A/h	/	/	2x 12v 157A/h	2x 12v 110A/h	/

DIMENSION & WEIGHT

Length	mm	1000	1000	1000	1000	1000	1000
Width	mm	480	480	480	480	550	550
Height	mm	1060	1060	1060	1060	1060	1060
Number of brushes and diameter	mm	1x Ø430	1x Ø430	1x Ø430	1x Ø430	1x Ø500	1x Ø500
Squeegee width	mm	700	700	700	700	800	800
Weight of the machine (without batteries/water/operator)	kg	91	80	85	65	91	80
Weight of the batteries (approx.)	kg	44	/	/	2x35	44	/



DELUX

MODEL TECHNICAL SPECIFICATION		DELUX 50 ET	DELUX 50 BM	DELUX 55/1 B	DELUX 55/2 B	DELUX 60 B	DELUX 55 BR
Scrubbing width	mm	500	500	550	550	600	505
Cleaning capacity up to	m ² /h	1700	1700	2100	2100	2400	2100
Operating range	h	/	2/3	5	5	5	5
Solution tank capacity		45	45	48	48	48	48
Recovery tank capacity	l	45	55	55	55	55	55

TECHNICAL DATES

Mechanical drive (front/rear)		rear	rear				
Forward speed	km/h	0/3.5	0/3.5	0/4	0/4	0/4	0/4
Max. slope	%	10	10	10	10	10	10
Water lift	(mm H ₂ O)	1800	1500	1800	1800	1800	1800
Brush pressure	kg	25/45	25/45	20/35	20/35	20/35	25/45
Noise level	dB	72	72	72	72	72	72

ELECTRIC DATES

Power	v	230	24	24	24	24	24
Vacuum motor		230v 550w	24v 550w	24v 550w	24v 550w	24v 550w	24v 800w
Brush motor		230v 550w	24v 500w	1x24v / 200w	2x24v / 200w	1x24v / 650w	1x24v / 650w
Traction motor		/	24v 100w	24v 130w	24v 130w	24v 130w	24v 130w
Voltage		/	2x 12v 157A/h	2x 12v 157A/h	2x 12v 157A/h	2x 12v 157A/h	2x 12v 157A/h

DIMENSION & WEIGHT

Length	mm	1000	1000	1350	1300	1300	1160
Width	mm	550	550	595	615	710	610
Height	mm	1060	1060	1040	1040	1040	1040
Number of brushes and diameter	mm	1x Ø500	1x Ø500	1x Ø550	2x Ø265	2x Ø305	n°2 rulli Ø110
Squeegee width	mm	800	800	750	750	850	800
Weight of the machine (without batteries/water/operator)	kg	85	65	105	105	105	105
Weight of the batteries (approx.)	kg	/	2x35	2x35	2x35	2x35	2x35

